Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Revision Date: 08.08.2022 Version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

TK.150130.00000 Catalog No. **Product Name Diethyl Ether** Cas no 60-29-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial use. Use as a laboratory reagent. Scientific research and development.

1.2.2. Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Name	TEKKİM KİMYA SAN. TİC. LTD. ŞTİ.
Street	ORGANİZE SAN. BÖL. MAVİ CAD. 8. SOK. NO :1 NİLÜFER / BURSA
Telephone	0224 243 21 71
E-mail	erhan@tekkim.com.tr
Company Representative	Erhan DİLER

1.4 Emergency Telephone Number +90 506 990 36 86

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Flammable liquids, Category 1 Acute toxicity, Oral, Category 4 Specific Target Organ Toxicity - Single exposure, Category 3, Central nervous system

For the full text of the H and EUH statements referred to in this section, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 (CLP) Hazard pictograms



Signal word (SEA) DANGER

Hazard Statements (SEA)

H224 Extremely flammable liquid and vapour.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

Precautionary Statements (SEA)

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.

P233 Keep container tightly closed.

P240 Ground/connect container or receiving equipment.

P241 Use explosion-proof electrical/ventilation/igniter/.../ material.

Intervention

P301+P312 IF SWALLOWED: Call 114 POISON CENTER or doctor/physician if you feel unwell. P403+P233 Store in a well-ventilated area. Keep container tightly closed.

SECTION 3: Composition/information on ingredients





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66 Factory: istoc 33.ada No: 47-49-51-53 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

теккім

Revision Date: 08.08.2022 Version 2 Classification according to Regulation (EC) No. 1272/2008 (CLP)

31	Maddeler	

3.1 WIAUUEIEI	
EC No	200-467-2
Molar mass	74.12 g/mol
Cas No	60-29-7
Concentration	(<= 100 %)
SECTION 4: First aid measures	

4.1 Description of first aid measures

General information	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Following inhalation	Remove casualty to fresh air and keep warm and at rest
Following skin contact	Wash with plenty of water. Take off contaminated clothing.
Following eye contact	Rinse carefully and thoroughly with eye wash or water.

Please give up to two glasses of water. Get immediate medical attention.

Following ingestion

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

There is no restriction for this item.

5.2 Special hazards arising from the substance or mixture

Flammable. Heavy-than-air vapors may form on the floor surface. May form explosive mixture with air at intense temperatures. In case of fire, dangerous flammable gases or vapors may develop. There may be glare. Attention please.

5.3 Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus..

5.4 Additional information

Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Don't breathe vapours,aerosols.Avoid substance contact. Keep away from head and source of ignition. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures,consult an expert.

6.2 Environmental precautions

Do not discharge into sewer. Risk of explosion.

6.3 Methods and material for containment and cleaning up

Close drainage channels. Take up with liquid-absorbent material. Clean the affected area.

6.4 Reference to other sections

Disposal: see section 13.

6.5 Additional information

Clear spills immediately.





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Revision Date: 08.08.2022 Version 2

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Advices on safe handling

Observe label precautions. Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advices on general occupational hygiene

Change contaminated clothing. Wash hands after working with substance. It is recommended to use a skin protection cream.

7.2 Conditions for safe storage, including any incompatibilities

OFOTION OF France company and the last and a methods

Storage conditions

Keep container tightly closed in dry and well-ventilated places. Protect from light. Keep away from heat and anything that can cause ignition.

7.3 Specific end uses

There are no other specific uses other than those mentioned in section 1.2.

SECTION	8: Exposure controls / personal protection	
8.1 Control parameters Diethylether		(60-29-7)
TR MAK	Acceptable maximum concentration (MAK)	400 mbp 1,200 mg / m3
TR OEL	Another time unless specified, 15 for a minute not to be exceeded upper limit of exposure value (STEL):	200 mbp 616 mg / m3
	8 hour set for reference time measured or calculated time weighted average (TWA)	100 mbp 308 mg/m3
8.2 Expos	sure controls	
Annronri	ata anginaaring controls	

Appropriate engineering controls

More attention should be paid to technical measures against the use of personal protective equipment.

Personal protection equipment

- Eye/face protection
- Safety glasses

Hand protection

Hand protection

Splash contact Glove material : Viton (R) Glove thickness :0,70 mm Break through time : > 30 minute

The protective gloves to be used must comply with the specifications of directive 89/686/EEC and the related standart EN374.

Other skin protection





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

текім

Flame reterdant antistatic protective chlothing.

Respiratory protection

Required when vapors are generated. Recommended filter type: AX (EN 371) SECTION 9: Physical and chemical Properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour Odour threshold pH value Melting point/freezing point Freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Upper/lower flammability or explosive limits Upper/lower flammability or explosive limits Vapour pressure Vapour density Density Relative density Water solubility (g/l) Fat solubility (g/l) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature

Liauid Transparent Characteristic No information. No information. -116 °C No information. 34.6 °C 1.013 hPa -40 °C No information. 175 °C 1,7 % (V) 36 %(V) 587 hPa 20 °C No information. 0,71 - 0,72 g/cm3 20 °C No information. 68 g/L 20 °C No information. log POW : 1.1 Bioacumulation isnot expected. No information. No information.

Version 2

Revision Date: 08.08.2022

Viscosity

Kinematic viscosity Dynamic viscosity Explosive properties Oxidising properties

SECTION 10: Stability and Reactivity

10.1 Reactivity

The formation of peroxides is possible. Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is stable under storage at normal room temperatures. Contains stabilizer: Butyl hydroxytoluene (<0.001 - 0.0009 %)

None

No information. 0,195 mPa.s 20 °C

Not classified as explosive.

10.3 Possibility of hazardous reactions

Reacts with air to release peroxide.

10.4 Conditions to avoid

Light. Heat. Air. to temperate. Moisture.

10.5 Incompatible materials

Rubber, various plastics.

10.6 Hazardous decomposition products

Peroxides.

SECTION 11: Toxicological information

11.1 Information on toxicological effects





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Revision Date: 08.08.2022 Version 2

Acute oral toxicity LD50 Rat: 1.215 mg/kg (RTECS) Symptoms: Risk of aspiration with vomiting. Inhalation may cause pulmonary edema and pneumonitis.

Acute inhalation toxicity LC50 Inhalation - Mouse - 4 h - 97.5 mg/l (RTECS) Symptoms: mucosal irritations

Acute dermal toxicity LD50 Rabbit: > 20,000 mg/kg (ECHA)

Skin irritation Rabbit Result: No irritation. OECD Test Guideline 404 Dermatitis, skin burning Repeated exposure may cause skin dryness and cracking.

Specific Target Organ Toxicity - Single exposure May cause drowsiness or dizziness. Target Organs: Central nervous system

11.2 Additional information

If inhaled: Cough, chest pain, difficulty breathing, dizziness, drowsiness. In case of contact with eyes: Redness, tearing, blurred vision. Prolonged or repeated exposure of the skin causes dryness and inflammation of the skin. Handle in accordance with safety and hygiene rules.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 Leuciscus idus (Golden orpheus): 2,840 mg/l; 48 hours (ECOTOX Database)

Toxicity to daphnia and other aquatic invertebrates EC50 Daphnia magna (Water flea): 1,380 mg/l; 48 hours (IUCLID)

Toxicity to algae (algae) static test EC50 Desmodesmus subspicatus (green algae): > 100 mg/l; 72 hours OECD Test Guideline 201

Toxicity to bacteria static test EC50 active waste: 21,000 mg/l; 3 hours OECD Test Guideline OECD 209 Static test NOEC active waste: 42 mg/l; 3 hours OECD Test Guideline OECD 209

12.2 Persistence and degradability

It does not dissolve easily in nature by itself.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB.





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

12.6 Other adverse effects

Discharge into environment must be avoided.

SECTION 13: Disposal considerations

Waste treatment methods

It must be disposed of in accordance with national and local regulations. Do not mix with other products. Uncleaned Treat packages as if it were the product itself ... Waste materials must be disposed of in accordance with national and local regulations.

SECTION 14: Transport information					
ADR	IMDG	ΙΑΤΑ	ADN	RID	
14.1 UN number					
UN 1155	UN 1155	UN 1155	UN 1155	UN 1155	
14.2 UN proper shipp	ping name				
DIETHYL ETHER	DIETHYL ETHER	DIETHYL ETHER	DIETHYL ETHER	DIETHYL ETHER	
14.3 Transport hazard class(es)					
3	3	3	3	3	
14.4 Packing group			1		
44 E Environmentel I		I	I	I	
14.5 Environmental hazards					
NO	NO	NO	NO	NO.	
No information available.	No information available.	No information available.	No information available.	No information available.	

14.6 Special Precautions for User:

No information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental legislation specific for the substance or mixture

This product safety data sheet complies with the requirements of EU Regulation 1907/2006.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been conducted for this substance.

SECTION 16: Other informations

Full text of H statements
H224 Extremely flammable liquid and vapour.
H302 Harmful if swallowed.
H336 May cause drowsiness or dizziness.
Person Who Prepared the Safety Data Sheet:

Name:

Certificate Number and Date: Communication information: Erhan DİLER 11.29.03 & 11 Şubat 2020 05069903686





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an 🔣 group company www.tekkim.com.tr | tekkim@tekkim.com.tr
 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31



Revision Date: 08.08.2022 Version 2