Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Revision Date: 26.09.2022 Version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

1.1 Product identifier	
Catalog No.	TK.911012.00000
Product Name	Formaldehyde Solution %37 (Stabilized min. %10 Methanol)
Cas no	50-00-0
1.2.1. Relevant identifie	d uses of the substance or mixture and uses advised against ed uses ic research and development. Use as laboratory reagent.
1.2.2. Uses advised ag No information available	
1.3. Details of the sup	plier of the safety data sheet
Name	TEKKİM KİMYA SAN. TİC. LTD. STİ.

Name	TEKKIM KIMYA SAN. TIC. LTD. ŞTI.
Street	ORGANİZE SAN. BÖL. MAVİ CAD. 8. SOK. NO :1 NİLÜFER / BURSA
Telephone	0224 243 21 71
E-mail	erhan@tekkim.com.tr
Company Representative	Erhan DİLER

1.4 Emergency Telephone Number +90 506 990 36 86

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Acute toxicity, Category 3, Oral Acute toxicity, Category 3, If inhaled Acute toxicity, Category 3, Dermal Skin corrosion, Category 1B Skin sensitization, Category 1 Germ cell mutagenicity, Category 2 Carcinogenicity, Category 1B Specific Target Organ Toxicity - Single exposure, Category 1, Eyes Specific Target Organ Toxicity - Single exposure, Category 3, Respiratory system

For the full text of the H and EUH statements in this section, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 (CLP) Hazard pictograms





Signal word (SEA) DANGER

Hazard Statements (SEA)

H350 May cause cancer.

- H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H341 Suspected of causin
- H370 Causes damage to organs (Eyes).

Precautionary Statements (SEA)





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Revision Date: 26.09.2022 Version 2



Prevention

P280 Wear protective gloves / goggles / and protective clothing. P201 Obtain special instructions before use.

Intervention

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do not try to hesitate.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: If breathing is difficult, remove victim to fresh air and keep comfortable for breathing easily. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for a few minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 If exposed or concerned: Get medical advice / attention.

SECTION 3: Composition/information on ingredients

Classification according to Regulation (EC) No. 1272/2008 (CLP)

EC No	200-001-8
Molar mass	30.03 g/mol
Cas No	50-00-0
Concentration	(37 % - 40 %)
SECTION 4: First aid measures	

4.1 Description of first aid measuresGeneral informationIn case of accident or unwellness, seek medical advice immediately
(show directions for use or safety data sheet if possible).Following inhalationRemove to fresh air. Call a doctor. If breathing stops: apply mechanical
respiration immediately, with oxygen if necessary.Following skin contactWash with plenty of water. Take off contaminated clothing.Following eye contactIn case of contact with eyes, rinse immediately with plenty of water and
consult an ophthalmologist.Following ingestionPlease give up to two glasses of water. Get immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water. Foam. Dry extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

There is no restriction for this item.

5.2 Special hazards arising from the substance or mixture

Heavy vapors from the air may occur on the floor surface. May form explosive mixture with air at intense temperatures. In the event of fire, dangerous flammable gases or vapors may develop.

5.3 Advice for firefighters

Special protective equipment for firefighters

Do not stay in dangerous zone without self-contained breathing apparatus. Keep a safe distance to cut off contact with skin and wear suitable protective clothing.

5.4 Additional information

Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr
 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Revision Date: 26.09.2022 Version 2

Advice for non-emergency personnel: Don't breathe vapours, aerosols. Avoid substance contact. Keep away from head and source of ignition. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

Close drainage channels. Take up with liquid-absorbent material. Clean the affected area.

6.4 Reference to other sections

Disposal: see section 13.

6.5 Additional information

Clear spills immediately.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Advices on safe handling

Observe label precautions. Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advices on general occupational hygiene

Change contaminated clothing. Wash hands after working with substance. It is recommended to use a skin protection cream.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in dry and well-ventilated places. Metal packaging should not be used.

7.3 Specific end uses

There are no other specific uses other than those mentioned in section 1.2.

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Formaldehyde		(50-00-0)
TR MAK	Ceiling value:	5 mbp 6 mg / m3
Methanol		
TR MAK	Acceptable	(67-56-1)
	maximum concentration (MAK)	200 mbp 260 mg / m3
TR OEL	8 hour specified for reference time measured or calculated time weighted average (TWA):	200 mbp 260 mg / m3

8.2 Exposure controls

Appropriate engineering controls

More attention should be paid to technical measures against the use of personal protective equipment.

Personal protection equipment

Eye/face protection Fully fitting safety glasses *Hand protection*



Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Hand protection

Full contact Glove material : Nitrile rubber Glove thickness :0,40 mm Break through time : >480 minute

Splash contact : Glove material : polychloroprene Glove thickness :0,65 mm Break through time : >240 minute

The protective gloves to be used must comply with the specifications of directive 89/686/EEC and the related standart EN374

Other skin protection

Flame reterdant antistatic protective chlothing.

Respiratory protection

Required when vapors are generated. Recommended filter type : Filter ABEK

SECTION 9: Physical and chemical Properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour Odour threshold pH value Melting point/freezing point Freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Upper/lower flammability or explosive limits Upper/lower flammability or explosive limits Vapour pressure Vapour density Density Relative density Water solubility (g/l) Fat solubility (g/l) Partition coefficient: n-octanol/water	Liquid Transparent No information. 0,05 - 0,125ppm 2,8 - 4,0 20 °C < -15 °C No information. 93 - 96 °C 1.013 hPa 62 °C No information. No information. 7 %(V) 73 %(V) No information. 1,09 g/cm3 20 °C No information. 30 g/cm3 20 °C No information. No information. Soluble. No information. No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
= · · · · · · · · · · · · · · · ·	

Viscosity

Kinematic viscosity Dynamic viscosity Explosive properties Oxidising properties No information. No information. Not classified as explosive. none

SECTION 10: Stability and Reactivity

10.1 Reactivity

Vapours may form explosive mixtures with air. Section 10.3 to see. Polymerization hazard.

10.2 Chemical stability

Sensitive to light. The product is stable under storage at normal ambient temperatures.





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr
 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31



Revision Date: 26.09.2022 Version 2

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



10.3 Possibility of hazardous reactions

There is a risk of explosion with nitromethane, performic acid, acids, phenol, nitric acid, hydrogen peroxide, peracetic acid, nitrogen dioxide.

Revision Date: 26.09.2022

Version 2

It can react exothermicly with bases, nitrides, polymerization initiators, sodium hydroxide, potassium permanganate, furfuryl alcohol, strong oxidizing agents.

Hydrochloric acid creates dangerous gases or vapors in contact with magnesium carbonate.

10.4 Conditions to avoid

Exposure to light. Strong heating.

10.5 Incompatible materials

Various metals, various alloys, mild steel, Copper

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity LD50: 212.77 mg / kg Symptoms: If swallowed, there is a risk of perforation of the esophagus and stomach with severe burning of the mouth and throat.

Acute inhalation toxicity

Symptoms: mucosal irritations, Cough, Shortness of breath, Inhalation may cause edema of the respiratory system. Possible damages :, damage to the respiratory system Acute toxicity estimate: 6.55 mg / l; 4 hrs; steam

Acute dermal toxicity Acute toxicity estimate: 638.47 mg / kg Acute toxicity estimate: 638.51 mg / kg

Skin irritation Its mixture causes burns. Blistering Cracking, fissure

Eye irritation The mixture causes serious eye damage. Blindness risk! Lacrimal irritation due to vapors.

CMR effects Carcinogenicity: Possible carcinogen. Mutagenicity: Evidence of a genetic disorder

Specific Target Organ Toxicity - Single exposure The mixture causes damage to organs. Target Organs: Eyes The mixture may cause respiratory irritation. Target Organs: Respiratory system **11.2 Additional information**





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015
 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

теккім

Systemic effects:

Revision Date: 26.09.2022 Version 2

Inebriation, Dizziness, Headache, Drowsiness, acidosis, drop in blood pressure, agitation, spasms, Visual disturbances, narcosis, Coma Handle in accordance with good industrial hygiene and safety practice.

Components

Formaldehyde Acute oral toxicity LD50 Rat: 100 mg / kg (Source)

> Acute inhalation toxicity Acute toxicity estimate: 3.1 mg / l; steam

Acute dermal toxicity Acute toxicity estimate: 300.1 mg / kg

Methanol

Acute oral toxicity Acute toxicity estimate: 100.1 mg / kg

LDLO human: 143 mg / kg (RTECS)

Acute inhalation toxicity LC50 Rat: 131.25 mg / l; 4 hrs; steam (ECHA)

Acute dermal toxicity LD50 Rabbit: approx 17,100 mg / kg

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB.

12.6 Other adverse effects

Discharge into environment must be avoided.

ISO 9001:2015

ISO 14001:2015

SECTION 13: Disposal considerations

Waste treatment methods

Group of Companies

It must be disposed of in accordance with national and local regulations. Do not mix with other products. Uncleaned Treat packages as if it were the product itself ... Waste materials must be disposed of in accordance with national and local regulations.

SECTION 14:	Transport info	ormation		
ADR	IMDO	G IATA	ADN	RID
14.1 UN numb	per			
		Tekkim is accred ISO 9001:2015 and ISC	Factory: 0.5 Factory: 0.5 Factory: 0.5 Factory: 0.5	mya Sanayi ve Ticaret Limited Şirketi 6.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA TURKEY 243 21 71 (pbx) Fax: +90 224 242 97 66 oc 33.ada No: 47-49-51-53

www.tekkim.com.tr | tekkim@tekkim.com.tr

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



(REACH)		Revision Date: 26.09.2	2022 Version 2	
UN 2209	UN 2209	UN 2209	UN 2209	UN 2209
14.2 UN proper shippi	ing name			
FORMALDEHYDE SOLUTION with not less than 25% formaldehyde.	FORMALDEHYDE SOLUTION with not less than 25% formaldehyde.	FORMALDEHYDE SOLUTION with not less than 25% formaldehyde.	FORMALDEHYDE SOLUTION with not less than 25% formaldehyde.	I FORMALDEHYDE SOLUTION with not less than 25% formaldehyde.
14.3 Transport hazard	l class(es)			
8	8	8	8	8
	, Letter the second sec			
14.4 Packing group		Ш	Ш	Ш
			m	m
14.5 Environmental ha		VEO	YES	YES
YES	YES	YES	110	110
No information available.	No information available.	No information available.	No information available.	No information available.

14.6 Special Precautions for User:

No information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental legislation specific for the substance or mixture

This product safety data sheet complies with the requirements of EU Regulation 1907/2006.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been conducted for this substance.

SECTION 16: Other informations

Full text of H statements

H350 May cause cancer.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

ECHNIC

- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H341 Suspected of causin
- H370 Causes damage to organs (Eyes).

Person Who Prepared the Safety Data Sheet:

Name:
Certificate Number and Date:
Communication information:

Erhan DİLER 11.29.03 & 11 Şubat 2020 05069903686



Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015